



Hexagon Brass Spacer

Type	Thread T	A/F	Length * L mm																							
HBS	M2	4.0	5	6	7	8	9	10	12	13	14	15	16	17	18	20	25	30	35	40	-	-	-	-	-	-
HBS	M2.5	5.0	5	6	7	8	9	10	12	13	14	15	16	17	18	20	25	30	35	40	45	50	-	-	-	-
Thread depth		Y	Tapped Through														8	10	15	15	15	15	-	-	-	-
HBS	M3	5.0	5	6	7	8	9	10	12	13	14	15	16	17	18	20	25	30	35	40	45	50	55	60	70	80
HBS	M3	5.5	5	6	7	8	9	10	12	13	14	15	16	17	18	20	25	30	35	40	45	50	55	60	70	80
HBS	M4	7.0	5	6	7	8	9	10	12	13	14	15	16	17	18	20	25	30	35	40	45	50	55	60	70	80
HBS	M5	8.0	5	6	7	8	9	10	12	13	14	15	16	17	18	20	25	30	35	40	45	50	55	60	70	80
Thread depth		Y	Tapped Through														10	10	15	15	15	15	15	15	15	15

Material: Brass Finish: Electro-nickel plated

All dimensions in mm

Hexagon Steel Spacer

Type	Thread T	A/F	Length * L mm																								
HSS	M3	5.0	5	6	7	8	9	10	12	13	14	15	16	17	18	20	25	30	35	40	45	50	55	60	70	80	
HSS	M3	5.5	5	6	7	8	9	10	12	13	14	15	16	17	18	20	25	30	35	40	45	50	55	60	70	80	
HSS	M4	7.0	5	6	7	8	9	10	12	13	14	15	16	17	18	20	25	30	35	40	45	50	55	60	70	80	
HSS	M5	8.0	5	6	7	8	9	10	12	13	14	15	16	17	18	20	25	30	35	40	45	50	55	60	70	80	
Thread depth		Y	Tapped Through														10	10	15	15	15	15	15	15	15	15	
HSS	M6	10.0	-	-	-	-	-	10	12	13	14	15	16	17	18	20	25	30	35	40	45	50	55	60	70	80	
Thread depth		Y	-	-	-	-	-	Tapped Through										10	10	15	15	15	15	15	15	15	15

Material: Mild Steel Finish: Electro-Zinc plated Yellow passivate

All dimensions in mm

Hexagon Nylon Spacer

Type	Thread T	A/F	Length * L mm																							
HNS	M2.5	5.5	5	6	7	8	9	10	12	13	14	15	16	17	17	20	25	30	35	-	-	-	-	-	-	-
HNS	M3	6.0	5	6	7	8	9	10	12	13	14	15	16	17	17	20	25	30	35	-	-	-	-	-	-	-
HNS	M4	8.0	5	6	7	8	9	10	12	13	14	15	16	17	17	20	25	30	35	-	-	-	-	-	-	-
HNS	M5	10.0	-	-	-	-	-	10	12	13	14	15	16	17	17	20	25	30	35	40	-	-	-	-	-	-
HNS	M6	10.0	-	-	-	-	-	10	12	13	14	15	16	17	17	20	25	30	35	40	-	-	-	-	-	-
Thread depth		Y	Tapped Through														10	10	10	10	-	-	-	-	-	-

Material: Glass reinforced Nylon Colour: Black/natural Max Temp: 110°

All dimensions in mm

How to order: **HBS — M3 — 5.0 — 25**

* Non-standard body lengths available on request.

