



**NOTES:**

1. MATERIAL: NYLON 6/6 UL 94 V-0 (RMS-019)
2. COLOR: BLACK.
3. TO FIT IN A  $\varnothing 7.9 \pm .002$  [ $\varnothing 3.13 \pm 0.05$ ] THREADED HOLE.  
 MINIMUM RECOMMENDED PANEL THICKNESS: 6 mm [.236]  
 PART CAN ALSO FIT NON THREADED HOLE DIA. 7 mm [.276]
4. PART DESIGNED IN mm, ALTERNATE UNITS FOR REFERENCE ONLY.
5. TOOL REQUIRED FOR INSTALLATION, AND PHILIPS SCREWDRIVER FOR REMOVAL.

			TITLE: <b>BARBED PUSH FASTENER, REMOVABLE</b>						DWG IN mm [IN]			
CREATED USING SOLIDWORKS			FILE #: BPFR-1		DWN: SK		APP: S.K.		FINAL			
GENERAL TOLERANCE UNLESS OTHERWISE NOTED			SHEET: 1 OF 1		SHEET SIZE: A		DT: 07/01/08		CHKD: D.Z.		PART #	PRINT TYPE
NOTED ±0.25 ANG. ±1°			RE: RICHCO, INC, --		RICHCO, INC. ENG@RICHCO-INC.COM (773) 539-4060				BPFR-1		CA	
A	RELEASED FOR PRODUCTION		SK	12/19/08								
REV.	DESCRIPTION		ENGR.	DATE								